

Polar Extrem

gültig ab / valid from
04.07.2023

0,59 W/m²K

U-Wert
U-value

0,37 W/m²K

U-Wert mit ISO-Oberdeckel
U-value with ISO upper lid

Version	A	A	B	C	D
	Lukenkasten frame size L x B x H in mm	Rohbaumaß rough opening size L x B in mm	lichte Raumhöhe floor to ceiling height in mm	Ausklappraum fold-out space in mm	Grundmaß basic size in mm
88 / 58	880 x 580 x 130	890 x 590	max. 2650	500	1150
88 / 68	880 x 680 x 130	890 x 690	max. 2650	500	1150
88 / 78	880 x 780 x 130	890 x 790	max. 2650	500	1150
114 / 55	1130 x 540 x 130	1140 x 550	max. 2750	650	1200
114 / 70	1130 x 690 x 130	1140 x 700	max. 2750	650	1200
120 / 60	1190 x 590 x 130	1200 x 600	max. 2800	550	1200
120 / 70	1190 x 690 x 130	1200 x 700	max. 2800	550	1200
130 / 70	1290 x 690 x 130	1300 x 700	max. 2800	450	1200
140 / 70	1390 x 690 x 130	1400 x 700	max. 2800	350	1200

